

Journal of Mechanical Engineering Advancements

Contents available at: <u>https://www.swamivivekanandauniversity.ac.in/jmea/</u>

A Multi-Plane Analysis of Dynamic Pressure Distribution Unveiling the Energetic Flow on a Wind Turbine Blade

Basma Souayeh^{1,2*} and Arijit Chandra³

¹Department of Physics, College of Science, King Faisal University, PO Box 400, Al-Ahsa, 31982, Saudi Arabia; basma.souayeh@gmail.com ²Faculty of Sciences of Tunis, University of Tunis El Manar, 2092 Tunis, Tunisia. ³Astram Technologies, 38 Virginia Street, Centurion – 0157.

Abstract

This study delves into the dynamic pressure distribution across a horizontal wind turbine blade, employing numerical simulations to unravel its energetic flow intricacies. Our analysis uncovers distinct pressure peaks and suctions at various blade cross-sections, reflecting the interplay of airfoil design and relative velocity. Moreover, the investigation exposes nuanced variations across different planes, shedding light on the influence of blade geometry and operational conditions. This exploration underscores the importance of understanding dynamic pressure for optimizing blade design and enhancing wind turbine efficiency, thus contributing to sustainable energy generation.

Keywords: HAWT, Aerodynamic Properties, Turbulence properties, Numerical Modeling

1. Introduction

The increasing global demand for clean and sustainable energy has propelled the exploration and utilization of renewable resources, with wind energy emerging as a prominent contender in this transition. Among the diverse array of wind turbines, horizontal axis wind turbines (HAWTs) have risen to prominence owing to their versatility and efficient power generation capabilities. This study delves into the intricate realm of HAWTs, scrutinizing their design principles, performance drivers, and technological advancements.

A pivotal aspect of HAWT optimization lies in the aerodynamic design of rotor blades, which significantly influences energy capture. Researchers have conducted extensive studies on blade shapes, materials, and configurations to enhance performance and efficiency. Works by Hansen et al. [1] offer valuable insights into aerodynamic principles and innovative blade designs. Various factors, including wind speed, turbulence, and site-specific conditions, exert a profound influence on HAWT performance. Talavera et Al. [2] have explored the impact of these factors on efficiency and reliability, while Mahmoud et al. [3] and Ala et al. [4] have investigated advanced control strategies to optimize

^{*}Author for correspondence

turbine operation under diverse wind conditions. Continual technological advancements have driven the evolution of HAWTs, making them more efficient, reliable, and cost-effective.

Studies by Teng et al. [5] highlight the development of innovative materials such as carbon fiber composites, while Thomas et al. [6] discussed the integration of smart technologies for enhanced predictive maintenance and performance optimization. A central focus of research revolves around the aerodynamic optimization of HAWT blades. Sharma et al. [7] explore the intricate relationship between blade design, wind speed, and power output, utilizing computational fluid dynamics (CFD) simulations for virtual testing and optimization. Other related CFD studies can be found in Ramesh et al. [8] research papers.

Studies by Kusiak et. al. [9] and Gonzales et al. [10] focus on maximizing energy production and minimizing losses within wind farms, while Nyugen et al. [11] and Khamies et al. [12] explore advanced control algorithms and grid stability strategies.

Exciting developments in HAWT technology include floating offshore wind farms, bio-composites, and hybrid renewable energy systems, all aimed at improving efficiency and adaptability. Environmental and social impacts are also under scrutiny, with studies by Erickson et al. [13] assessing visual and ecological concerns. This paper aims to comprehensively analyze dynamic pressure distribution around HAWT blades, shedding light on the distinctive flow dynamics underlying their operation. By elucidating the potential and challenges associated with HAWTs, this study contributes to efforts aimed at optimizing blade design, overcoming performance hurdles, and integrating advanced technologies. Ultimately, it underscores the crucial role of HAWTs in addressing the global demand for clean and sustainable energy solutions.

2. Computational Technique

In this investigation, a three-bladed horizontal wind turbine design with specific blade geometry and airfoil sections is considered. The blade undergoes a transition from a cylindrical form near the hub to incorporate distinct airfoils at different sections along its span. The computational approach involves the utilization of SolidWorks for blade modeling and Ansys for meshing and flow domain discretization. The resulting mesh structure exhibits favorable quality metrics, ensuring accurate simulation outcomes.

The boisterous wind cascades in the direction opposing the positive z-axis, as illustrated in the above diagram depicting the blade's orientation in Fig. 1, characterized by a velocity of 12 m/s—a standard wind speed for a turbine of this magnitude. Envisioning the incoming flow as the maestro, It directs the blade's graceful revolution with an angular velocity of -2.22 rad/s around the z-axis. The three-dimensional model, crafted for computational efficiency, deliberately omits the inclusion of the hub to alleviate numerical intricacies, allowing the problem to unfold with a touch of simplicity. Additionally, to keep the study resource-friendly, a single blade is selected for this particular simulation.

The Table 1 displays the geometry arrangement chosen for the investigation. The three-dimensional model of the turbine blade is designed with the help of SolidWorks modeling software using the parameters mentioned in Table 1. After that, the blade model was imported to the geometry module of Ansys. Then, after importing the geometry to the Ansys, it was transferred to the meshing component in order to discretize the flow domain. A denser mesh structure formed in close proximity to the blade structure utilizing the inflation layer (Fig 3). The domain consists of 75675 numbers of modes and 378543 numbers of elements. The average skewness and average orthogonal quality were found to be 0.28 and 0.76, respectively, which indicate that the mesh quality is well within acceptable limits.



Fig. 1 Three-dimensional model of wind turbine blade

Element	r/R	Twist °	C/R	Airfoil
1	0.075	42	0.0614	
2	0.125	32	0.06826	
3	0.175	23	0.07452	
4	0.225	15	0.07782	S818
5	0.275	11.5	0.07543	
6	0.325	8.2	0.07188	
7	0.375	7	0.06832	
8	0.425	6	0.06479	
9	0.475	5	0.06126	
10	0.525	4	0.05771	
11	0.575	4.15	0.05415	S825
12	0.625	3.85	0.05062	
13	0.675	3.25	0.04707	
14	0.725	2.75	0.0436	
15	0.775	1.25	0.04024	
16	0.825	0.75	0.03704	
17	0.875	0.55	0.03385	
18	0.925	0.85	0.03066	S826
19	0.975	0.05	0.02747	

Table	1. Blade	geometry
-------	----------	----------



Fig. 2 Cut section view of mesh near blade surface

3. Results and discussions

In the grand ballet of fluids, a hidden partner joins the waltz of pressure – dynamic pressure. Unlike its static counterpart, a constant presence pressing against surfaces, dynamic pressure is the energetic dancer, a manifestation of the fluid's motion. It carries the kinetic energy within its swirling steps, dictating the interplay between velocity and pressure in a mesmerizing flow choreography. Imagine a river rushing downstream. The faster the water flows, the more energy it carries. This kinetic energy isn't just a theoretical concept; it translates into an increase in dynamic pressure. Deeper into the river, where the flow slows, the dynamic pressure dips, showcasing the intimate relationship between velocity and its energetic signature. Dynamic pressure plays a crucial role in shaping the behavior of fluids in fascinating ways. It drives phenomena like Bernoulli's principle, where an increase in velocity leads to a decrease in pressure, explaining the lift generated by airplane wings. It also governs the force generated by jets in jet engines, where high-velocity fluids create significant dynamic pressure, propelling the engine forward. The significance of dynamic pressure becomes particularly evident in the world of wind turbine blades. As the blades spin, they interact with the flowing air, creating complex dynamic pressure distributions across their surfaces. Understanding these distributions is crucial for optimizing turbine performance.

At the blade tip, where the wind speed is highest, dynamic pressure peaks due to the increased flow velocity. This high pressure contributes to lift generation, propelling the blade forward and driving the turbine's rotation. However, it can also lead to the formation of tip vortices, swirling regions of low pressure that can cause unwanted noise and reduce efficiency. Moving towards the root of the blade, the wind speed and, consequently, the dynamic pressure decrease. This translates to a decrease in lift generation but also reduces the intensity of tip vortices. By analyzing the dynamic pressure distribution across different cross-sections, engineers can optimize blade design to maximize lift while minimizing unwanted effects like noise and vibrations.

Furthermore, studying dynamic pressure in conjunction with static pressure can offer deeper insights into the flow behavior around the blade. The total pressure, the sum of dynamic and static pressure, remains constant along a streamline (except for energy losses due to friction). Analyzing the variations in total pressure along different streamlines can reveal flow separation, boundary layer characteristics, and other crucial aspects of wind turbine aerodynamics. In conclusion, dynamic pressure is not just a mathematical abstraction; it is the energetic partner in the flow's ballet,

carrying the kinetic energy and influencing the behavior of fluids in profound ways. By understanding its significance, we can unlock the secrets of efficient wind turbine design, harness the power of flowing air, and generate clean energy with greater precision and control. As we delve deeper into the intricate dance of dynamic pressure, we pave the way for a future powered by a deeper understanding of the fluid world around us.



Fig. 3 Contour plot 1 of Dynamic Pressure at Different Sectional Plane along Span of Blade

All four planes exhibit a prominent dynamic pressure peak near the leading edge of the blade tip. This is expected behavior due to the higher relative velocity experienced by the tip, leading to an increase in kinetic energy and, consequently, dynamic pressure. All planes also show a significant suction peak (negative dynamic pressure) on the backside of the airfoil, particularly towards the tip. This suction area corresponds to the low-pressure region generated by the airfoil's shape and contributes to lift generation.



Fig. 4 Contour plot 2 of Dynamic Pressure at Different Sectional Plane along Span of Blade

The intensity of both pressure and suction peaks decreases as we move from the tip towards the root. This is because the relative velocity and lift generation decrease along the blade's span. There are subtle differences in the dynamic pressure distribution patterns across the different planes. For instance, the 15-meter plane appears to have a more pronounced pressure peak at the tip compared to the others. This suggests the influence of additional factors beyond simple location on the blade.

The dynamic pressure distribution suggests potential tip vortex formation, particularly at the 15-meter plane. Further investigation into the velocity field and vorticity around the tip is crucial for understanding and mitigating this phenomenon. Analyzing the dynamic pressure distribution in conjunction with static pressure and lift/drag coefficients can offer insights into the overall aerodynamic forces and torque generated by the blade. This information is crucial for optimizing blade design and turbine performance. Analyzing the dynamic pressure distribution under different wind speeds and turbulence conditions would provide a more comprehensive understanding of the blade's performance across diverse operational scenarios. Investigating the distribution of dynamic pressure on the pressure and suction sides separately could offer deeper insights into the lift and drag generation mechanisms, potentially informing strategies for noise reduction.

By delving deeper into these aspects, we can gain a more nuanced understanding of the dynamic pressure distribution on the wind turbine blade and its impact on performance. This knowledge can contribute to the development of more efficient and optimized wind turbine designs, driving cleaner and more sustainable energy generation.

4. Conclusions

The observed dynamic pressure distribution on the wind turbine blade highlights the crucial role of kinetic energy in shaping flow characteristics and influencing performance. The prominent pressure peak at the tip signifies efficient lift generation, while the suction peak on the backside underscores the importance of airfoil design. However, subtle variations across the planes and the presence of potential tip vortices indicate the need for further investigation into blade geometry and operational conditions to optimize performance and minimize unwanted effects. By comprehensively understanding and harnessing the power of dynamic pressure distribution, we can design more efficient wind turbines, paving the way for a cleaner and more sustainable future.

5. References

1. Hansen M. Aerodynamics of Wind Turbines, 2nd edition. Earthscan. 2008;

8. Ramesh K, Mebarek-Oudina F, Souayeh B. Mathematical Modelling of Fluid Dynamics and Nanofluids. Mathematical Modelling of Fluid Dynamics and Nanofluids. 2023.

9. Kusiak A, Song Z. Design of wind farm layout for maximum wind energy capture. Renew Energy. 2010;

10. González JS, Rodríguez ÁGG, Mora JC, Burgos Payán M, Santos JR. Overall design optimization of wind farms. Renew Energy. 2011;

11. Nguyen HM, Naidu DS. Advanced control strategies for wind energy systems: An overview. In: 2011 IEEE/PES Power Systems Conference and Exposition, PSCE 2011. 2011.

^{2.} Talavera M, Shu F. Experimental study of turbulence intensity influence on wind turbine performance and wake recovery in a low-speed wind tunnel. Renew Energy. 2017;

^{3.} Mahmoud MS, Oyedeji MO. Adaptive and predictive control strategies for wind turbine systems: A survey. IEEE/CAA Journal of Automatica Sinica. 2019.

^{4.} Ala A, Mahmoudi A, Mirjalili S, Simic V, Pamucar D. Evaluating the Performance of various Algorithms for Wind Energy Optimization: A Hybrid Decision-Making model. Expert Syst Appl. 2023;

^{5.} Teng H, Li S, Cao Z, Li S, Li C, Ko TJ. Carbon Fiber Composites for Large-Scale Wind Turbine Blades: Applicability Study and Comprehensive Evaluation in China. J Mar Sci Eng. 2023;

^{6.} Thomas L, Ramachandra M. Advanced materials for wind turbine blade- A Review. In: Materials Today: Proceedings. 2018.

^{7.} Sharma P, Gupta B, Pandey M, Sharma AK, Nareliya Mishra R. Recent advancements in optimization methods for wind turbine airfoil design: A review. In: Materials Today: Proceedings. 2020.

 Khamies M, Magdy G, Hussein ME, Banakhr FA, Kamel S. An Efficient Control Strategy for Enhancing Frequency Stability of Multi-Area Power System Considering High Wind Energy Penetration. IEEE Access. 2020;
Erickson WP, Wolfe MM, Bay KJ, Johnson DH, Gehring JL. A comprehensive analysis of small-passerine fatalities from collision with turbines at wind energy facilities. PLoS One. 2014;